



⑦	OUTER MOLDED	BLACK 45P PVC	0.028	KG
⑥	INTER MOLDED	LDPE	0.028	KG
⑤	FERRITE CORE	F5B:RH12*20*7.3	2	PCS
④	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	2	PCS
③	CONNECTOR	DVI 18+1/M BLACK INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
②	CONNECTOR	HDMI A TYPE MALE BLACK INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	(1P*30#+D+AL+MYLAR)*4C+1P*30#+3C*30#+ADB OD:6.0±0.15 JACKET:BLACK PVC	5	M
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

1:100% short and open testing.

2:Test conditions  
DC300V /10MS  
Insulation resistance 10MΩ(Min)  
Conduction resistance 5Ω(Max)

Ltemref	Quantity	Title/Name,designation,material,dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale	
		MARCH 4.2012	DVI 18+1/M TO HDMI/M L=5M	MARCH 4.2012	FREE	
				26-1686		
				26-1686	Edition 1	Sheet 1/2